



Pump Model Selection Guide

Centrifugal Pumps CF-S

CF	-	6	S	4	-	F	-	M	M	M	-	GP	-	20	-	BD
Type		Suction size (inches)		Discharge size (inches)		Bearing assembly		Liner / Impeller / Seal box material				Auxiliaries				
CF = Centrifugal SCF = Smart CF		1.5 2 3 4 6 8 10 12 14 16 20		1.5 2 3 4 6 8 10 12 14 18		B B C C, D D, E E, F F, S S, G S, G, T G, T T		M = 27 % Cr white iron A = 28 % Cr, pH > 3 C = 30 % Cr, pH > 10 L = 35 % Cr, Low C pH > 1 T = Special high wear X = X-Type high wear S = Stainless steel 4 = Cd4MCu F = Ferralium I = Ductile Iron K = 36% Cr, Low C H/T pH > 1 R = Natural rubber E = EPDM B = Butyl H = Hypalon N = Neoprene U = Urethane				DC = Direct coupling BD = Belt drive DC-EM = Direct Coupling, Electric Motor BD-EM = Belt Drive, Electric Motor				
Series		Impeller type		Seal type												
S		20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36		GP = Gland Packing EP = Expeller MS = Mechanical seals												

Information without engagement. All rights to changes without prior notice reserved.

