



Pump Model Selection Guide

Centrifugal Pumps CF-S

CF	-	6	S	4	-	F	-	M	M	M	-	GP	-	20	-	BD
Type		Suction size (inches)		Discharge size (inches)		Liner / Impeller / Seal box material					Auxiliaries					
CF = Centrifugal SCF = Smart CF		1.5 2 3 4 6 8 10 12 14 16 20		1.5 2 3 4 6 8 10 12 14 18		M = 27 % Cr white iron A = 28 % Cr, pH > 3 C = 30 % Cr, pH > 10 L = 35 % Cr, Low C pH > 1 T = Special high wear X = X-Type high wear S = Stainless steel 4 = Cd4MCu F = Ferralium I = Ductile Iron K=36% Cr, Low C H/T pH > 1 R=Natural rubber E=EPDM B=Butyl H=Hypalon N=Neoprene U=Urethane					DC = Direct coupling BD = Belt drive DC-EM = Direct Coupling, Electric Motor BD-EM = Belt Drive, Electric Motor					
Series		Bearing assembly		Seal type					Impeller type							
S		B B C C, D D, E E, F F, S S, G S, G, T G, T T		GP = Gland Packing EP = Expeller MS = Mechanical seals					20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36							

Information without engagement. All rights to changes without prior notice reserved.

